

Portable Oxygen Concentrator Comparison



Arya Mini



Arya Airtivo Max



Arya Go



Arya Q Powered by Drive



Oxlife Liberty 2



Oxlife Independence



Sequal Eclipse 5



	Arya Mini	Arya Airtivo Max	Arya Go	Arya Q Powered by Drive	Oxlife Liberty 2	Oxlife Independence	Sequal Eclipse 5
Oxygen Mode Delivery	Pulse Flow Only	Pulse Flow Only	Pulse Flow Only	Pulse Flow Only	Pulse and Continuous Flow	Pulse and Continuous Flow	Pulse and Continuous Flow
Oxygen Output	Pulse Flow 1 - 4	Pulse Flow 1 - 6	Pulse Flow 1 - 5	Pulse Flow 1 - 5	Pulse Flow 1 - 10 Continuous 0.5 - 2 LPM	Pulse Flow 1 - 6 Continuous 0.5 - 3.0 LPM	Pulse Flow 1 - 9 Continuous 0.5 - 3.0 LPM
Dimensions	8.26" H 6.2" D 3.4" W	6.3" H 3.3" D 8.7" W	10" H 3.1" D 7.3" W	8.4" H 3.5" D 8.6" W	9.9" H 3.8" D 9.9" W	20.2" H 8.0" D 10.9" W	19.3" H 7.1" D 12.3" W
Weight	3.3 Pounds	4.37 Pounds	6 Pounds	5 Pounds	7.5 Pounds	19.4 Pounds	18.4 Pounds
Expected Battery Life	Up to 7.2 Hours	Up to 5.4 Hours	Up to 16 Hours	Up to 5.4 Hours	Pulse Flow Up to 4.5 Hours Continuous Up to 2 Hours	Pulse Flow Up to 6 Hours Continuous Up to 5.25Hours	Pulse Flow Up to 5.4 Hours Continuous Up to 3.7 Hours
Battery Recharge Time	Up to 6 Hours (12 Cell Battery)	Up to 4 Hours	Up to 6 Hours (16 Cell Battery)	Up to 3 Hours	Up to 2.5 Hours	Up to 2.5 Hours	Up to 5 Hours
Noise Level	40 dBA	49 dBA	43 dBA	40 dBA	44.4 dBA	40 dBA	40 dBA
Carrying Options	Shoulder or Handle Strap,	Shoulder or Handle Strap, Backpack	Shoulder or Handle Strap, Backpack Harness	Shoulder or Handle Strap	Shoulder or Handle Strap,	Wheeled Travel Cart	Wheeled Travel Cart
Operating Temperature Range	41° F - 158° F	41° F - 104° F	41° F - 104° F	41° F - 104° F	50° F - 104° F	50° F - 104° F	41° F - 104° F
Operating Humidity Range	Up to 90% Humidity	Up to 90% Humidity	Up to 95% Humidity	Up to 93% Humidity	Up to 85% Humidity	Up to 95% Humidity	Up to 95% Humidity
Operating Altitude Range	0 - 10,000 Feet	0 - 10,000 Feet	0 - 10,000 Feet	0 - 13,000 Feet	0 - 13,123 Feet	0 - 13,123 Feet	0 - 13,123 Feet
O2 Concentration	90% (-3%/+5.5%)	90% (-3%/+6%)	90% (-3%/+5.5%)	90% (-3%/+4%)	87% - 95%	90% (-3%/+6%)	90% (+/-5%)
Power	100 - 240 VAC, 50/60 Hz, 11 - 16 VDC	100 - 240 VAC, 50/60 Hz, 14.4 VDC	100 - 240 VAC, 50/60 Hz, 12 - 24 VDC	100 - 240 VAC, 50/60 Hz, 13.8 - 17 VDC	100 - 240 VAC, 50/60 Hz, 2.5 A	100 - 240 VAC, 50/60 Hz, 12 - 15 VDC	100 - 240 VAC, 50/60 Hz, 12 - 19 VDC
FAA Approved	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Warranty	3 Years - Lifetime	3 Years - Lifetime	3 Years - Lifetime	5 Years - Lifetime	3 Years	5 Years	3 Years